



WATERZONE SERIES

The clearly better ozone water disinfection system.

Custom systems built to your exact specifications.

FEATURES OF WATERZONE SERIES:

- 10 - 200 grams / hour ozone production
- Generates high dissolved ozone levels
- Easy and simple installation
- Automated system
- Very efficient with excellent mass transfer of ozone
- Produces ozone from integrated oxygen concentrator
- Central switch starts and stops system
- Includes stainless steel tank, pump and piping
- Compact design
- Water flow from 1 - 300 gpm
- Ready-to-use upon delivery

WATERZONE SYSTEMS	OZONE OUTPUT (G/HR)	OZONE DOSAGE RATES	MAX FLOW RATE (GPM)	TANK (GAL)
Waterzone-20	20	2.9 ppm @ 30 gpm - 5.9 ppm @ 15 gpm	30	15
Waterzone-40	40	3.5 ppm @ 50 gpm - 7.0 ppm @ 25 gpm	50	25
Waterzone-80	80	2.5 ppm @ 140 gpm - 5.0 ppm @ 70 gpm	100	50
Waterzone-100	100	2.2 ppm @ 200 gpm - 4.4 ppm @ 100 gpm	200	100
Waterzone-150	150	2.2 ppm @ 300 gpm - 4.4 ppm @ 150 gpm	300	140
Waterzone-200	200	2.9 ppm @ 300 gpm - 5.9 ppm @ 150 gpm	300	140

OPTIONAL EQUIPMENT	DESCRIPTION
AS-500 Dissolved Ozone Monitor	Monitors and controls ozone levels in the water (ppm)
ORP Meter	Monitors ORP level in water, will also control ozone levels with indirect reading
Remote Ambient Ozone Monitor	Monitors ozone levels near water point-of-use for safety purposes
Ozone Destruct Unit	Destroys all undissolved ozone from the contact tank and includes water trap
Air Compressor	Provides compressed air for oxygen concentrator which eliminates the need for compressed air supply (not available for Waterzone-60 and larger)
50 Hz Power	Necessary for overseas use

- Other options and larger systems available.
- The above specifications are contingent upon near perfect condition (transfer efficiency above 85%, water pH neutral, clean and chlorine free water, etc.).
- Contact Ozone Solutions for more information on these and our other products.

